

# **Novo**Touch

## Full-featured detachable PC module designed exclusively for the NovoTouch collaborative and interactive flat panel displays

#### Features

- Full-featured detachable PC module for seamless integration into the NovoTouch interactive flat panel display
- Powerful 8<sup>th</sup> generation Intel<sup>®</sup> Core<sup>™</sup> processor with integrated Intel<sup>®</sup> UHD graphics chipset
- Supports fast SSD and DDR4 RAM in a variety of configurations (Varies by model)
- HDMI-Out (4K@30Hz) for connection to secondary display
- Up to five (5) high speed USB ports (USB-v2 (x2) (USB-v3 (x2) (USB 3.1 Type C (x1) for connectivity to a variety of devices including but not limited keyboards, mice and flash drives
- Integrated RJ45 port for network monitoring and management solutions
- Reduces clutter & promotes a cable-free workplace
- Easy installation and maintenance
- Rugged steel chassis for extra strength and integrity
- Kensington<sup>®</sup> security slot for prevention against theft or unapproved removal

### Photos



# Specifications

Model Number	odel Number		VKW30-i5	VKW30-i7
Product Compatibility	EK653i, EK753i, EK863i			
Туре	Detachable PC Module			
Operating System	Windows 10 Recommend (Not Included)			
Interface	80PIN Connector			
Hardware	CPU (Intel <sup>®</sup> 8 Generation CPU)		Intel <sup>®</sup> Core™ i5-8265U 1.6GHz	Intel <sup>®</sup> Core™ i7-8565U 1.8GHz
	RAM		DDR4 8GB	DDR4 8GB
	Storage (M2. SSD)		256GB	256GB
	Graphics (Integrated)		Intel <sup>®</sup> UHD Graphics 620	
	Sound Card		Integrated High Definition Audio Stereo	
	Networking		Integrated 10/100/1000Mbps Adaption	
Connectivity	Input	Audio	Microphone-In (3.5mm)	
	Output	Display	HDMI-Out v1.4 (4K@30Hz)	
		Audio	Audio-Out (3.5mm)	
	Ethernet		RJ45	
	USB		USB 2.0 (x2), USB 3.0 (x2), USB 3.1 Type C (Gen 2)(Data Only)	
	Wireless		802.11ac (2.4GHz/5GHz)	
	Bluetooth		V4.2	V4.2
LED Indicator	HDD LED, Power LED			
Buttons	Power Button, System Recovery Button			
Environmental Conditions	Operating Temperature		0°C - 45°C (32°F - 113°F)	
	Operating Humidity		10% - 90% RH	
	Storage Temperature		-20°C - 60°C (-4°F - 140°F)	
	Storage Humidity		10% - 90% RH	
Power	Power Supply		Internal Power Supply Module	
	Power Requirements		12 - 19V, DC 5.0A	
	Max Power		60W	
	Standby Power		1.2W	
Accessories	Antennas (x2), Documentation Kit			
Security	Kensington® Security Slot, TPM2.0			
Available Color	Black			
Weight	0.74kg (1.6lbs)			
Dimensions (L x W x H)	202 v 122	.5 x 30mm (7.9 x 5.3' x	1 21)	



